



10021 Amarillo Blvd. East • Amarillo, Texas 79108-7542  
Toll Free (877) 827-8255 • Toll Free Fax (877) 827-7363  
(806) 374-3747 • FAX (806) 335-3717

We appreciate your interest in our Precast Concrete Above Ground (AG) Storm Shelters. We offer two styles of Above Ground Storm Shelters available in varying sizes. The first thing to consider is which style is best suited for your site conditions and needs. Below is a description of each style and attached are drawings for your reference.

### **Above Ground (AG) Storm Shelters Manufactured Per NSSA Standard**

- Wheelchair accessible
- No ladder or stairs to climb when entering or exiting the Shelter
- None or minimal excavating required for installation
  - **Stand Alone Version**
    - Advantages
      - Ease of installation, Shelter does not require any anchoring
        - Shelter only requires that the ground at the desired location is compact and level
        - In the event that you move to another property, this Shelter can be relocated with a boom truck/crane
    - Quick Facts
      - Only available in one size
        - 6'W x 6'L x 7'H I.D., 7'W x 7'L x 8'H O.D. (Model #SS-606070-AG)
      - Assembled Shelter weighs approximately 24,800 lbs.
      - Location must be accessible for our boom truck/crane to set it in place
        - We need to back our boom truck up to within 14 ft. of the Shelter's location
        - Site must be clear of overhead power lines, trees or any other obstructions
  - **Epoxy To Concrete Slab Version**
    - Advantages
      - In most cases, we can avoid use of a boom truck by using our "Donkey/Mule" to set them
        - The "Donkey/Mule" is a device that drives inside the Shelter, lifts it up and moves it and sets it in place on your concrete slab/foundation
    - Quick Facts
      - Available in 3 sizes
        - 3'-0"W x 6'-0"L x 5'-2.375"H Inside Dimensions (Model #SS-3060-AG)
        - 5'-4"W x 6'-4"L x 6'-3.75"H Inside Dimensions (Model #SS-5363-AG)
        - 7'-1"W x 7'-1"L x 6'-3.75"H Inside Dimensions (Model #SS-7070-AG)
      - Shelter epoxies directly to an existing concrete slab
        - Most patios and garage slabs are acceptable
        - We do not supply the concrete slab for these units.
        - We recommend that the slab must be at least 6" thick
        - Slab to extend a minimum of 6" beyond the outside width and length of the Shelter, we recommend 18" beyond the outside width & length
        - We will epoxy your Shelter to your existing concrete slab at time of delivery

We highly recommend that you come by and see the storm shelters that we have on display at our plant. The display is located at our entrance and can be looked at anytime. Our plant is located at 10021 Amarillo Blvd East in Amarillo, TX (map attached). This will give you an opportunity to see the shelters up close and visit with our staff in person between the hours of 7:30AM-5:30PM M-F or Saturday by appointment only.

We look forward to helping you with all your Storm Shelter needs and hope to hear from you soon!

Thank You!

Vaughn Concrete Products, Inc.