



**CONSEAL™**  
Concrete Sealants INC.

**CS-50**

Liquid Butyl Primer

**APPLICATIONS**

Concrete surface preparation coating and installation aid for bonding preformed sealants to concrete structures and metal structures. Can be applied in advance of product installation.

**SEALING PROPERTIES**

When applied to concrete or metal, ConSeal CS-50 Liquid Butyl Primer creates a butyl rubber film that acts to both seal the structure and improve the bond between preformed sealants and the structure.

**PHYSICAL PROPERTIES**

Color:	Black
% Solids:	25% minimum
Solvent Type:	Hexane
Flash Point:	76°F
Weight/Gallon:	7.6 Pounds
Dry Time @ 77°F (25°C):	15-20 minutes
Dry Time @ 40°F (4°C):	30-40 minutes
Clean Up:	Mineral Spirits
Coverage Per Gallon:	Approx. 300 sq ft on wet cast concrete
Min. Storage Temperature:	32°F
Min. Application Temperature:	0°F
Surface When Dry:	Flat Black, non-tacky
Shelf Life	6 months

**LIMITED WARRANTY**

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.